

Tender Notice for the Sale of HET-090 Culligan High Efficiency Twin Water Softener System

Town of Big River is inviting offers for the purchase a **HET-090 Culligan High Efficiency Twin Water Softener System**.

This water softener system was installed at the Big River Community Centre in February 2020 and was used for approximately 10 months. Since December 2020, the system has not been used, as the Town of Big River now receives water supplied through reverses osmosis. As a result, the system is in like-new condition.

Viewing Information:

To arrange a viewing of the system, please contact the Town Office at (306) 469-2112.

Tender Bid Forms:

Tender bid forms are available at:
Town of Big River Municipal Office
606 1st Street North
Phone: (306) 469-2112
Email: office@townofbigriver.ca

Submission of Offers:

Written offers must be submitted to the Town Office by **no later than noon on January 17, 2025**.

Offers may be submitted in the following ways:

- **By Mail:** Town of Big River, Box 220, Big River, SK S0J 0E0
- **In person:** Deliver sealed envelope to 606 1st Street North, Big River, SK

***All tenders must be clearly labeled "Tender for HET-090 Culligan High Efficiency Twin Water Softener System" on the outside of the envelope. The envelope must be sealed, with the signature and date written across the seal.**

Office hours are Monday to Friday, 8:30 a.m. to 4:30 p.m. Closed for lunch from noon to 1:00 p.m.

Please Note: The lowest or any offer may not necessarily be accepted.



Markets Served:

- Clinics
- Educational Facilities
- Energy / Power
- Food / Beverage Production
- Food Service / Restaurants
- Grocery
- Healthcare / Hospitals / Bio-Pharmaceutical
- Hospitality / Lodging
- Manufacturing
- Municipal Drinking Water
- Oil / Gas

The Culligan® High Efficiency (HE) Twin Series WATER SOFTENER SYSTEM

A Continuous Flow of Soft Water with a Smart Choice

The High Efficiency (HE) Twin softener with patented technology delivers improved efficiency to reduce operating costs. The HE Twin softener reduces hard water contaminants*, reducing scale build-up that affect equipment performance. The HE twin configuration consists of two independent mineral tanks, which provide a continuous flow of soft water 24 hours a day. With the Culligan® Smart Controller, available on the HE Twin, the softener adjusts to influent water conditions and regenerates based on need. Customers can also monitor their water treatment system performance, consumable usage, and maintenance needs, at a single site or across multiple ones 24 hours a day.

The HE Twin softener is part of the Culligan® Commercial and Industrial Solutions that combine durable and efficient equipment, systems experience, and technical experts who understand your unique requirements. From planning your system to installing your water treatment equipment, Culligan® Commercial and Industrial Solutions offer options that help deliver the quality of water to meet your needs. Contact Culligan® today to learn more about the HE Twin softener system.

CULLIGAN® COMMERCIAL & INDUSTRIAL ADVANTAGES:

- Simple System Integration
- Global Product Platform
- Flexible Configurations
- Quick Delivery / Easy Installation
- Exclusive Culligan Advanced Electronics
 - Historical Operating Data
 - Alarm Recognitions
 - US Standard and Metric Readings
 - Remote Monitoring Options
 - Telemetry Options

*Contaminants may not necessarily be in your water.



PRE-TREATMENT SOLUTIONS.

SYSTEM SPECIFICATIONS

Examples of Softener Applications

- RO / DI Pretreatment
- Apartment buildings, assisted living facilities and hotels — Quality water for laundry, dishwashers, boilers
- Office buildings — For heating plant pretreatment, tenant convenience, general housekeeping
- Restaurants — For dishwashing, cleaning material savings, scale reduction
- Car washes — Quality results, detergent and water heating savings, scale reduction
- Grocery / Retail — Quality water for aesthetics and help extend equipment life
- Light industry — For process and make-up water, boiler and cooling system pretreatment, general housekeeping

Warranty

Culligan's HE water softeners are backed by a limited 1-year warranty against defects in materials, workmanship, and corrosion. The plastic conditioner tank has a 5-year warranty. See printed warranty for details. †

Some localities have corrosive water. A softener cannot correct this condition, so its printed warranty disclaims liability for corrosion of plumbing lines, fixtures, or water-using equipment. If you suspect corrosion, your independently operated Culligan® dealer has equipment to help control the problem.

† See printed warranty for details. Culligan® will provide a copy of the warranty upon request.

Standard Features

- Alternating Twin Tank Design — allows for a continuous supply of softened water
- Culligan's Smart Controller — More control over your equipment with programming and monitoring capabilities typically found in more expensive PLC controls a variety of add-on options for advanced instrumentation and communication let you easily customize the system to help meet your needs
- Regeneration initiation by choice or combination of time clock, flow meter or Aqua-Sensor
- Telemetric Capability
- Corrosion Resistant Positive Motor-Driven Regeneration Valve — Motor driven piston is reliable under server water conditions, resists dirt, iron and turbidity
- Corrosion Resistant Tanks — Made from fiberglass reinforced polyester
- Under-drain design enhances softening capacity and reduces pressure loss
- Multi-Poppet Design — Allows for easy service and increases durability and valve life
- Electronic By-Pass - The softener can be by-passed electronically either from the unit or from the remote monitor and automatically goes back into service after a pre-set time.
- Flow Meter
- Tested and certified by WQA against NSF/ANSI 372, CSA B483.1 and NSF/ANSI Standard 61 for material requirements
- The Control Enclosure complies with UL 50/50E and UL 746C standards for a NEMA 3R Enclosure Rating

Optional Features & Accessories

- Dubl-Safe™ Brine System for softeners — Positive overflow protection Automatic refill control is backed up by shutoff float valve to reduce chance of overflow
- Patented Aqua-Sensor® Control — Initiates regeneration only when needed based upon water hardness. Automatically adjusts to changes in raw water hardness and water consumption
- Smart Brine Tank Probe - monitors salt usage and communicates how much salt is left.
- Skid Mounted System
- Remote Display
- RS232, RS485, Modbus PLC Output

System Specifications

Specification	US	Metric
Pipe Size, All Units	1.5"	
Maximum Operating Pressure	20–125 psig	135–860 kPa
Power Voltage Frequency Phase	24 50/60 Hz	
Feed Water Temperature	33–120° F	0–48° C
Power Consumption	3/100 Watts	
Vacuum	None ²	
Turbidity	5 NTU, max. ³	
Chlorine	1 mg/L, max. ³	
Iron	5 mg/L	

1 120 Volt/24 Volt CUL/UL listed Transformer Included.

2 Tank warranty is void if subject to vacuum.

3 See media specification for details.

HE Water Softener System

Model	Resin Qty. (RRL)	Flow Rates (gpm/lpm)		Tank Size*** (in/in)	
		Continuous*	Peak**	Softener	Brine****
HET-060	2	25.1	31.5	14 x 47	18 x 38
	56.6	98.0	119.2	358 x 1,194	457 x 965
HET-090	3	26.6	35.2	16 x 53	24 x 40
	85	100.7	133.2	408 x 1,346	610 x 1,016
HET-120	4	23.3	31.8	16 x 65	24 x 40
	112.3	88.2	120.4	408 x 1,651	610 x 1,016
HET-150	5	27.2	35.8	18 X 65	24 X 50
	141.6	103.0	133.5	457 x 1,651	610 x 1,270
HET-210	7	28	37.4	21 X 62	24 X 50
	198.2	106.0	141.8	533 x 1,575	610 x 1,270

*Flow rate at a 15 psi pressure loss.

**Flow rate at a 25 psi pressure loss.

***Dimensions are diameter by tank height.

****Brine systems are optional.

Flow rates shown are per tank.

Low flow channeling (flow rates less than 0.5 gallons per minute per cubic foot of resin) may cause hardness leakage into effluent.

www.culligan.com • 866-787-4293

For over 80 years, Culligan® has made better water. Our global network, comprised of 800+ dealers and international licensees in over 90 countries, is dedicated to addressing your water-related problems. As a worldwide leader in water treatment, our sales representatives and service technicians are familiar with the local water conditions in your area. Being global and local position us to deliver customized solutions to commercial and industrial water issues that affect your business and your bottom line.

All trademarks used herein are registered trademarks of Culligan International Company.

Products manufactured or marketed by Culligan and its affiliates are protected by patents issued or pending in the United States and other countries.

Culligan reserves the right to change the specifications referred to in this literature at any time, without prior notice.